

View Online at <https://aerobasegroup.com/nsn/5930-01-181-0054>

Thread Class:

2a single mounting facility

Thread Length:

6.50 millimeters single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

66.4 millimeters

Shaft Diameter:

6.4 millimeters single actuator

Shaft Length:

16.0 millimeters single actuator

Overall Diameter:

52.6 millimeters

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.438 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flat, undercut single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level and 30.0 amperes inductive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0