

View Online at <https://aerobasegroup.com/nsn/5930-01-181-1473>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Width Between Flats:**

0.188 inches single actuator and 0.191 inches single actuator

**Overall Length:**

1.707 inches

**Overall Height:**

Between 1.720 inches and 1.780 inches

**Overall Width:**

Between 1.345 inches and 1.405 inches

**First Flat Length:**

0.343 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.344 inches single actuator

**Nonturn Device Radius:**

0.406 inches at 9:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load highest ac voltage rating at sea level

**Style Designator:**

Rectangular panel mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0