## NSN 5930-01-181-1642

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-181-1642

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
1.000 inches
Overall Height:
2.450 inches
Overall Width:
0.750 inches
Body Length:
0.905 inches
Body Width:
0.655 inches
Body Height:
2.200 inches
Actuator Style:
Rectangular
Actuator Height:
0.250 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator and green single actuator
Illuminated Actuator Color Sequence:
Left half of actuator red right half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes
inductive ac and 1.000 amperes lamp ac
Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

15 tab, solder lug

## **Specification Data:**

813/10-mil-c-22885/58 government enecification

## NSN 5930-01-181-1642

Push Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0