

View Online at <https://aerobasegroup.com/nsn/5930-01-181-1643>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.000 inches

Overall Height:

2.450 inches

Overall Width:

0.750 inches

Body Length:

0.905 inches

Body Width:

0.655 inches

Body Height:

2.200 inches

Actuator Style:

Rectangular

Actuator Height:

0.250 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator and green single actuator

Illuminated Actuator Color Sequence:

Left half of actuator red right half of actuator green

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

15 tab, solder lug

Specification Data:

81349-mil-s-22885/58 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0