NSN 5930-01-181-1644

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-181-1644

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 1.000 inches |
| Overall Height: |
| 2.450 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.905 inches |
| Body Width: |
| 0.655 inches |
| Body Height: |
| 0.220 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.250 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Green single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes |
| inductive ac and 1.000 amperes lamp ac |
| |

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

15 tab, solder lug

Specification Data:

81349-mil-s-22885/58 government specification

Shelf Life:

N/a

NSN 5930-01-181-1644

Push Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A053a0