## NSN 5930-01-181-3354

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-181-3354

| Body Style:   |
|---|
| Panel mount   |
| Hazardous Locations/environmental Protection:                                   |
| Shock proof and watertight  |
| Overall Length:   |
| 2.120 inches  |
| Overall Height:   |
| 2.090 inches  |
| Overall Width:  |
| 1.750 inches  |
| Body Width:   |
| 1.750 inches  |
| Body Height:  |
| 1.620 inches  |
| Actuator Style:   |
| Round, flush  |
| Actuator Height:  |
| 0.310 inches  |
| Maximum Voltage Rating In Volts:  |
| 440.0 ac and 355.0 dc   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Nonpile-up Contact Arrangement:   |
| 2 pole, single throw, double make, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                           |
| 0.500 amperes inductive dc and 5.000 amperes inductive ac                       |
| Special Features:   |
| Legend plate reads luff e-run   |
| Terminal Type And Quantity:   |
| 4 tab w/screw   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A053a0  |