NSN 5930-01-181-4628

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-181-4628 |
|---|
| Thread Class: |
| 3a single threaded bushing |
| Thread Length: |
| 0.535 inches single threaded bushing and 0.565 inches single threaded bushing |
| Overall Length: |
| Between 1.170 inches and 1.200 inches |
| Body Diameter: |
| 0.320 inches |
| Body Length: |
| 1.000 inches |
| Tempurature Sensing Element Type: |
| Bulb |
| Width Across Flats: |
| 0.690 inches |
| Mounting Method: |
| Threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.4375 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 1.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 250.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level second voltage |
| Frequency In Hertz: |
| 60.0 first voltage |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Cylindrical |
| Thread Series Designator: |
| Unf single threaded bushing |

N/a

Shelf Life:

NSN 5930-01-181-4628

Thermostatic Switch - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0