Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-181-4641

Overall Length:
2.280 inches
Overall Height:
1.805 inches
Overall Width:
1.330 inches
Unthreaded Mounting Hole Diameter:
0.100 inches single mounting facility
Individual Section Quantity:
3
Longest Horizontal Distance Between Mounting Centers:
2.090 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
0.900 inches single mounting facility
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Actuator Type:
Thumbwheel all actuators
Features Provided:
Rfi shielding
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
10 all actuators
Terminal Type:
Printed circuit and tab, solder lug
Contact Load Current Rating:
0.2 amperes resistive load dc at sea level
Readout Indicator Marking:
0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section
Contact Arrangement Truth Table:
Bcd complement only, 1 pole - 10 positions each section
Color:
White each indicator marking
Precious Material And Location:
Stator surfaces gold
Precious Material:
Gold

Code Indicating Wheel Switch - Page 2 of 2

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A052b0

