

View Online at <https://aerobasegroup.com/nsn/5930-01-182-1694>

**Overall Length:**

3.640 inches

**Overall Height:**

3.120 inches

**Overall Width:**

3.120 inches

**Unthreaded Mounting Hole Diameter:**

0.265 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

2.280 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.280 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3380

**Style Designator:**

Tap, circuit selector

**Reference Number Differentiating Characteristics:**

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0