NSN 5930-01-182-1694



View Online at https://aerobasegroup.com/nsn/5930-01-182-1694 Overall Length: 3.640 inches Overall Height: 3.120 inches Overall Width:
3.640 inches Overall Height: 3.120 inches
Overall Height: 3.120 inches
3.120 inches
Overall Width:
3.120 inches
Unthreaded Mounting Hole Diameter:
0.265 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
2.280 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.280 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
450.0 ac at sea level
Rotor Through Connection Quantity:
1 each section
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Criticality Code Justification:
Feat

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

NSN 5930-01-182-1694

Rotary Switch - Page 2 of 2



Special	Features:
---------	-----------

Item must comply with requirements of defense supply center columbus production standard no. Lo3380

Style Designator:

Tap, circuit selector

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0