

View Online at <https://aerobasegroup.com/nsn/5930-01-182-2504>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and oiltight

Actuator Style:

Flexible

Actuator Diameter:

0.250 inches

Actuator Height:

4.900 inches

Housing Height:

1.780 inches

Housing Length:

3.130 inches

Housing Width:

1.540 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 two circuit, one position momentary single switch unit

Switch Release Force:

2.4 inch-ounces

Switch Actuating Force:

32.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 5.0 overtravel degrees and 6.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 0.600 amperes resistive ac

Special Features:

0.500 in. Electrical access port

Terminal Type And Quantity:

9 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0