NSN 5930-01-182-6719

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-182-6719 **Overall Length:** 9.250 inches **Overall Height:** 4.500 inches **Overall Width:** 2.938 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches single mounting facility **Individual Section Quantity:** 3 **Longest Horizontal Distance Between Mounting Centers:** 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.188 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Mounting Method:** Unthreaded hole single mounting facility **Features Provided:** Cam actuated **Contact Voltage Rating In Volts:** 600.0 highest dc voltage rating at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes each section periphery **Contact Load Current Rating:** 6.0 amperes resistive load lowest dc voltage rating at sea level and 4.0 amperes inductive load lowest dc voltage rating at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver

Shelf Life:

Style Designator: In-line, cam actuated

N/a

NSN 5930-01-182-6719Rotary Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A052b0