NSN 5930-01-183-3450

Rotary Switch - Page 1 of 2



n/5930-01-183-3450

| View Online at https://aerobasegroup.com/nsr |
|----------------------------------------------|
| Thread Length: |
| 0.312 inches single mounting facility |
| Overall Length: |
| 1.666 inches |
| First Flat Length: |
| 0.250 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.375 inches single actuator |
| Overall Diameter: |
| 0.687 inches |
| Individual Section Quantity: |
| 2 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 each section periphery |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level |
| Shaft Type: |
| Round, flat, undercut single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes each section periphery |
| Contact Load Current Rating: |
| 4.0 amperes resistive load ac at sea level |
| Style Designator: |
| Tap, circular, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

NSN 5930-01-183-3450Rotary Switch - Page 2 of 2



Fiig:

A052b0