NSN 5930-01-183-6755

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-183-6755

| Hole mounted |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.370 inches |
| Body Length: |
| 0.780 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.360 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.092 inches |
| Actuator Length: |
| 0.570 inches |
| Actuator Style: |
| Roller arm |
| Actuator Free Position Height: |
| 0.535 inches |
| Actuator Roller Diameter: |
| 0.190 inches |
| Actuator Roller Width: |
| 0.130 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 250.0 dc |
| End Application: |
| 4920-01-083-2644 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 0.5 ounces |
| Switch Actuating Force: |
| 6.3 ounces |
| Actuator Movement: |
| Between 0.157 pretravel inches and 0.031 overtravel inches and 0.031 differential inches |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| |

NSN 5930-01-183-6755

Sensitive Switch - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A053a0