## NSN 5930-01-183-6755

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-183-6755

| Hole mounted   |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Length:                |
| 0.370 inches   |
| Body Length:   |
| 0.780 inches   |
| Body Width:  |
| 0.250 inches   |
| Body Height:   |
| 0.360 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.092 inches   |
| Actuator Length:   |
| 0.570 inches   |
| Actuator Style:  |
| Roller arm   |
| Actuator Free Position Height:   |
| 0.535 inches   |
| Actuator Roller Diameter:  |
| 0.190 inches   |
| Actuator Roller Width:   |
| 0.130 inches   |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac and 250.0 dc  |
| End Application:   |
| 4920-01-083-2644   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded hole  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, both positions maintained single switch unit                       |
| Switch Release Force:  |
| 0.5 ounces   |
| Switch Actuating Force:  |
| 6.3 ounces   |
| Actuator Movement:   |
| Between 0.157 pretravel inches and 0.031 overtravel inches and 0.031 differential inches |
| Terminal Type And Quantity:  |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |
|  |

## NSN 5930-01-183-6755

Sensitive Switch - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A053a0