

View Online at <https://aerobasegroup.com/nsn/5930-01-184-0592>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Moisture proof and dusttight

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

30.0 milliamperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+135.00/+1500.00 actuation point pounds per square inch and +125.00/+1440.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0