

View Online at <https://aerobasegroup.com/nsn/5930-01-184-1482>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof and shock proof

Overall Length:

0.740 inches

Overall Height:

3.060 inches

Overall Width:

0.740 inches

Body Length:

0.740 inches

Body Width:

0.740 inches

Body Height:

Between 1.180 inches and 1.250 inches

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Width:

0.740 inches

Actuator Color:

Green single actuator and yellow single actuator and white single actuator and blue single actuator

Illuminated Actuator Color:

Green single actuator and yellow single actuator and white single actuator and blue single actuator

Actuator Inscription:

Go, no go, bit-aba single actuator

Illuminated Actuator Color Sequence:

Upper left half of actuator green upper right half of actuator yellow bottom half of actuator white

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination or 11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0