NSN 5930-01-184-6164

Gasket seal, threaded external single connection

Pressure Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-184-6164

3a single pressure connection
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
3.000 inches
Outside Diameter:
0.438 inches single connection
Body Length:
1.635 inches
Overall Diameter:
0.900 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.750 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Mounting Method:
Inlet connection
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Proof Pressure:
2295.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
110.00 actuation point pounds per square inch gage and 75.00 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:

NSN 5930-01-184-6164Pressure Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0