

View Online at <https://aerobasegroup.com/nsn/5930-01-184-6271>

Thread Class:

2a single mounting facility

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.2 amperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 0.1 amperes lamp load dc at sea level

Special Features:

Shaft has drilled slot 0.093 in. By 0.068 in. Located 0.468 in. From base of thd bushing

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0