

View Online at <https://aerobasegroup.com/nsn/5930-01-185-9900>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

5.750 inches

Overall Height:

10.938 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.062 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

5000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

2700.00 actuation point pounds per square inch gage and 220.00 differential point pounds per square inch gage and 390.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Shock resistant

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0