

View Online at <https://aerobasegroup.com/nsn/5930-01-185-9903>

Thread Class:

2b all pressure connection

Inside Diameter:

0.438 inches all connections

Overall Length:

5.531 inches

Overall Height:

6.844 inches

Overall Width:

2.688 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

80.00 pounds per square inch gage

Thread Size:

0.438 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+4.00/+35.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut

Contact Stimulus Rating:

5.00 actuation point pounds per square inch gage and 3.00 differential point pounds per square inch gage and 9.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Pressure Connector Type:

Plain, threaded internal all connections

Special Features:

Shock resistant

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0