## NSN 5930-01-186-0180



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-186-0180 **Body Style:** Panel mounted **Body Width:** 0.750 inches **Body Height:** 0.750 inches **Case Material:** Metal **Actuator Length:** 0.620 inches **Actuator Style:** Rectangular **Actuator Height:** 0.174 inches **Actuator Width:** 0.620 inches **Illuminated Actuator Color:** Red single actuator **Actuator Inscription:** Ccw single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Mounting Surface To Terminal End Distance:** 2.620 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac **Precious Material And Location:** Contact surfaces silver **Terminal Type And Quantity:** 

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:
8 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

-
Demilitarization:

No

## **NSN 5930-01-186-0180**Push Switch - Page 2 of 2



Fiig:

A053a0