NSN 5930-01-186-5539

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-186-5539

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.359 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

Between 1.000 inches and 1.306 inches

Individual Section Quantity:

12

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

9 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

9 single actuator

NSN 5930-01-186-5539

Rotary Switch - Page 2 of 2

A052b0



| Shaft Type: |
|---|
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Makes before breaks each section rear |
| Switch Actuator Positioning Increment: |
| 30.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 75.0 milliamperes resistive load ac at sea level |
| Style Designator: |
| Tap, circular, bushing mount |
| Test Data Document: |
| 81349-mil-dtl-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef single mounting facility |
| Specification Data: |
| 81349-mil-dtl-3786/4 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |