

View Online at <https://aerobasegroup.com/nsn/5930-01-186-5541>

Body Style:

Bushing mount

Overall Length:

0.775 inches

Overall Height:

2.828 inches

Overall Width:

0.650 inches

Bushing Length:

0.468 inches

Body Length:

0.775 inches

Body Width:

0.650 inches

Body Height:

1.120 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.220 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0