

View Online at <https://aerobasegroup.com/nsn/5930-01-186-7943>

**Thread Class:**

3a single threaded bushing

**Thread Length:**

0.440 inches single threaded bushing

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

4.633 inches

**Body Length:**

1.379 inches

**Overall Diameter:**

0.890 inches

**Temperature Sensing Element Type:**

Bulb

**Width Across Flats:**

0.890 inches

**Operating Temperature Rating:**

Between -100.0 degrees fahrenheit and 600.0 degrees fahrenheit

**Mounting Method:**

Threaded bushing

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.625 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

390.00 actuation point degrees fahrenheit and 10.00 differential point degrees fahrenheit and 55.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single threaded bushing

**Specification Data:**

81349-mil-s-24236/26 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0