

View Online at <https://aerobasegroup.com/nsn/5930-01-186-8207>

Hazardous Locations/environmental Protection:

Explosion proof and vibration resistant

Outside Diameter:

0.250 inches single connection

Mounting Slot Width:

0.344 inches

Distance Between Mounting Facility Centers:

3.156 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees celsius and 60.0 degrees celsius

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage5.0 amperes resistive load second voltage500.0 milliamperes resistive load third voltage500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+15.00/+250.00 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

125.0 ac at sea level first voltage250.0 ac at sea level second voltage125.0 dc at sea level third voltage250.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0