NSN 5930-01-186-9662

Hazardous Locations/environmental Protection:

Unthreaded Mounting Hole Diameter:

Explosion proof
Overall Length:
8.438 inches
Overall Height:
3.875 inches
Overall Width:
4.250 inches

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-186-9662

0.250 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
Longest Vertical Distance Between Mounting Centers:
3.625 inches
Tempurature Sensing Element Type:
Bulb
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
-40.00/+120.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point knob with scale
Contact Voltage Rating In Volts:
250.0 ac at sea level second voltage
Frequency In Hertz:
60.0 second voltage
Media For Which Designed:
Gas or liquid

NSN 5930-01-186-9662

Thermostatic Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0