

View Online at <https://aerobasegroup.com/nsn/5930-01-186-9662>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

8.438 inches

Overall Height:

3.875 inches

Overall Width:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Temperature Sensing Element Type:

Bulb

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

-40.00/+120.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob with scale

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0