

View Online at <https://aerobasegroup.com/nsn/5930-01-187-0088>

Thread Class:

2a

Body Style:

Hole mounted

Overall Length:

3.055 inches

Overall Height:

3.062 inches

Overall Width:

1.000 inches

Case Material:

Plastic

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.359 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

Housing Height:

1.750 inches

Housing Length:

3.055 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.922 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

6525-01-147-9531

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

Between 8.0 ounces and 16.0 ounces

Switch Actuating Force:

Between 24.0 ounces and 48.0 ounces

Actuator Movement:

0.141 pretravel inches and 0.125 overtravel inches and 0.060 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

0.500-14 nps conduit opening

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0