# NSN 5930-01-187-0088

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-187-0088

	<b>.</b> .
Thread	Class:

2a

**Body Style:** 

Hole mounted

**Overall Length:** 

3.055 inches

### **Overall Height:**

3.062 inches

#### **Overall Width:**

1.000 inches

**Case Material:** 

Plastic

Actuator Style:

Roller plunger

Actuator Free Position Height:

### 1.359 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

#### Housing Height:

1.750 inches

#### Housing Length:

3.055 inches

#### Housing Width:

1.000 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.922 inches

# Maximum Voltage Rating In Volts:

250.0 ac

# End Application:

6525-01-147-9531

# Inclosure Type:

Fully enclosed

# Mounting Method:

Threaded stud

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.138 inches

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-187-0088

Sensitive Switch - Page 2 of 2



Switch Release Force: Between 8.0 ounces and 16.0 ounces Switch Actuating Force: Between 24.0 ounces and 48.0 ounces **Actuator Movement:** 0.141 pretravel inches and 0.125 overtravel inches and 0.060 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac **Special Features:** 0.500-14 nps conduit opening **Thread Series Designator:** Unc **Terminal Type And Quantity:** 6 screw Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A053a0