# NSN 5930-01-187-5826

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-187-5826

#### **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

1.080 inches

#### **Overall Height:**

3.120 inches

#### **Overall Width:**

1.080 inches

#### **Body Length:**

0.688 inches

#### **Body Width:**

0.750 inches

#### **Case Material:**

Metal

# Actuator Length:

# 0.812 inches

Actuator Style:

Rectangular

## Actuator Height:

0.270 inches

#### Actuator Width:

0.812 inches

#### Actuator Color:

Green single actuator and white single actuator

#### **Illuminated Actuator Color:**

Green single actuator and white single actuator

#### **Actuator Inscription:**

Conversation mode/enabled single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# **Features Provided:**

Actuator seal

# Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

# Criticality Code Justification:

Afve

# NSN 5930-01-187-5826

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

## **Precious Material And Location:**

Contacts gold

# Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

### Fiig:

A053a0