

View Online at <https://aerobasegroup.com/nsn/5930-01-187-7850>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

Between 1.184 inches and 1.216 inches

**Overall Height:**

2.968 inches

**Overall Width:**

Between 0.944 inches and 0.976 inches

**Body Length:**

Between 1.075 inches and 1.205 inches

**Body Width:**

Between 0.859 inches and 0.891 inches

**Body Height:**

2.828 inches

**Actuator Length:**

Between 1.024 inches and 1.056 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.140 inches

**Actuator Width:**

Between 0.784 inches and 0.816 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Amber single actuator and green single actuator

**Illuminated Actuator Color Sequence:**

Top half of actuator amber bottom half of actuator green

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Horizontally split screen and two diffusers

**Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0