NSN 5930-01-187-8030

Push Switch - Page 1 of 2

Body Style:

Afve

Contact Load Current Rating At Maximum Rated Voltage:



View Online at https://aerobasegroup.com/nsn/5930-01-187-8030

| Overall Length: |
|---|
| 1.000 inches |
| Overall Height: |
| 2.388 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.905 inches |
| Body Width: |
| 0.655 inches |
| Actuator Length: |
| 0.680 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.188 inches |
| Actuator Width: |
| 0.430 inches |
| Actuator Color: |
| White single actuator and white single actuator |
| Illuminated Actuator Color: |
| White single actuator and white single actuator |
| Actuator Inscription: |
| Local remote single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| Recorder-reproducer set, signal data an/ush-3 (v) |
| Inclosure Type: |
| Fully enclosed |
| |
| Mounting Method: |
| Panel |
| |
| Panel Features Provided: Rfi shielding |
| Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: |
| Panel Features Provided: Rfi shielding |

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-187-8030

Push Switch - Page 2 of 2



| Terminal Type Ar | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0