

View Online at <https://aerobasegroup.com/nsn/5930-01-187-8573>

Inside Diameter:

0.250 inches all connections

Overall Length:

6.500 inches

Overall Height:

7.750 inches

Body Diameter:

7.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.000 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 110.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches all pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.00/+3.00 actuation point inches of water

Contact Adjustment Type:

External actuation point screw with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/bracket

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0