# NSN 5930-01-187-8581

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-187-8581



# **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

3.900 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

## **Body Width:**

0.680 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

## Actuator Height:

0.100 inches

# Actuator Width:

0.620 inches

## Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

8 single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

3.366 inches

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Holding solenoid and full display lens

# Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-187-8581

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

# Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0