## NSN 5930-01-188-1798

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-1798

view Chillie at https://aerobasegroup.com/hish/0330-01-100-1/30
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
0.990 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.990 inches
Body Width:
0.740 inches
Body Height:
Between 1.380 inches and 1.450 inches
Actuator Length:
0.990 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac
Precious Material And Location:
Terminal surfaces gold

Tommar danaged gold

## **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **NSN 5930-01-188-1798**Push Switch - Page 2 of 2

Fiig: A053a0



Terminal Type And Quantity:
11 pin
Specification Data:
81349-mil-s-22885/80 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No