# NSN 5930-01-188-2339

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-188-2339



# **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

# **Overall Length:**

Between 3.880 inches and 3.900 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

### **Body Width:**

0.680 inches

#### **Body Height:**

0.680 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.100 inches

# Actuator Width:

0.620 inches

### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

2 single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

3.366 inches

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

### Features Provided:

Holding solenoid and full display lens

# Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-188-2339

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

# **Precious Material And Location:**

Contacts silver

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0