## NSN 5930-01-188-2340

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-2340

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
Between 3.880 inches and 3.900 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.680 inches
Body Height:
0.680 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
3 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.366 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid and full display lens
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-188-2340

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0