NSN 5930-01-188-2342

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-2342

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
Between 3.880 inches and 3.900 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.680 inches
Body Height:
0.680 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
5 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.366 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid and full display lens
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-188-2342

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0