NSN 5930-01-188-2344

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-2344

Body Style:				
Panel mounted				
Hazardous Locations/environmental Protection:				
Explosion proof and humidity resistant				
Overall Length:				
Between 3.880 inches and 3.900 inches				
Overall Height:				
0.750 inches				
Overall Width:				
0.750 inches				
Body Width:				
0.680 inches				
Body Height:				
0.680 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.100 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
White single actuator				
Illuminated Actuator Color:				
White single actuator				
Actuator Inscription:				
B single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
Mounting Surface To Terminal End Distance:				
3.366 inches				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				
Holding solenoid and full display lens				
Nonpile-up Contact Arrangement:				
4 pole, double throw, both positions maintained single switch unit				

NSN 5930-01-188-2344

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

D۳	acione	Matoria	I And	Location:
71	ecious	wateria	II Ana	Location.

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0