

View Online at <https://aerobasegroup.com/nsn/5930-01-188-4229>

Thread Class:

2a single pressure connection

Overall Length:

5.188 inches

Overall Height:

5.406 inches

Overall Width:

2.812 inches

Body Height:

2.750 inches

Distance Between Mounting Facility Centers:

2.406 inches

Capillary Tube Length:

120.0 inches

Bulb Length:

3.625 inches

Bulb Diameter:

0.688 inches

Longest Horizontal Distance Between Mounting Centers:

3.281 inches

Shortest Horizontal Distance Between Mounting Centers:

2.750 inches

Intermediate Horizontal Distance Between Mounting Centers:

3.031 inches

Longest Vertical Distance Between Mounting Centers:

2.406 inches

Shortest Vertical Distance Between Mounting Centers:

0.656 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Facility Circle Radius:

0.281 inches

Operating Temperature Rating:

195.0 degrees fahrenheit

Mounting Method:

Flange and threaded hole

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fifth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+90.00/+165.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0