NSN 5930-01-188-5303

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-5303 **Thread Class:** 2a **Body Style:** Hole mount **Overall Length:** 1.906 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.625 inches **Overall Height:** 2.000 inches **Overall Width:** 0.797 inches **Body Length:** 1.234 inches **Body Width:** 0.797 inches **Body Height:** 0.750 inches **Case Material:** Plastic **Actuator Length:** 1.125 inches **Actuator Style:** Rectangular **Actuator Height:** 0.812 inches **Actuator Width:** 0.625 inches **Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 250.0 ac **End Application:** 6530-01-147-9531 **Inclosure Type:** Fully enclosed **Mounting Method:** Panel Thready Qty Per Inch (tpi):

32

Thread Size:

0.109 inches

NSN 5930-01-188-5303

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

Special Features:

Non-serrated actuator, gold contacts for dry circuit

Precious Material And Location:

Contacts gold

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0