NSN 5930-01-188-6644

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-188-6644

Th	rea	d (CI	ass:

2b single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.750 inches

Outside Diameter:

0.438 inches single connection

Overall Height:

10.938 inches

Overall Width:

3.000 inches

Body Length:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Shortest Vertical Distance Between Mounting Centers:

1.062 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Type:

External actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level fourth voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

NSN 5930-01-188-6644Pressure Switch - Page 2 of 2



Frequency In Hertz:
60.0 third voltage
Media For Which Designed:
Gas
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0