

View Online at <https://aerobasegroup.com/nsn/5930-01-188-8826>

Inside Diameter:

0.125 inches all connections

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.438 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Distance Between Mounting Facility Centers:

4.875 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

10.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+3.00/+11.00 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0