

View Online at <https://aerobasegroup.com/nsn/5930-01-188-8840>

Hazardous Locations/environmental Protection:

Explosion proof and weather resistant and vibration resistant

Overall Length:

4.250 inches

Overall Height:

5.031 inches

Overall Width:

3.875 inches

Body Height:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.281 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -180.0 degrees fahrenheit and 1000.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

-20.00/+120.00 actuation point degrees celsius

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0