## NSN 5930-01-189-3185

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-189-3185

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
4.920 inches
Overall Height:
2.094 inches
Overall Width:
1.570 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.660 inches
Actuator Roller Width:
0.190 inches
Housing Height:
1.560 inches
Housing Length:
3.700 inches
Housing Width:
1.570 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.190 inches
Maximum Voltage Rating In Volts:
480.0 ac and 230.0 dc
End Application:
Rast system
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:

18.0 ounces

## NSN 5930-01-189-3185

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:** 

0.400 amperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:** 

4 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0