NSN 5930-01-189-3583

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-189-3583

View Online at https://aerobasegroup.com/nsn/5930-01-189-3583
Overall Length:
2.200 inches
Outside Diameter:
0.250 inches single connection
Body Length:
1.550 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -25.0 degrees fahrenheit and 350.0 degrees fahrenheit
Mounting Method:
Line
Features Provided:
Internally grounded
Contact Action Stimulus:
Increase
Proof Pressure:
600.00 pounds per square inch gage
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, double make, both positions maintained
Terminal Type:
Wire lead
Contact Load Current Rating:
1.0 amperes lamp load single voltage
Contact Adjustability:
Contact Aujustability.
Actuation point adjustable
•
Actuation point adjustable
Actuation point adjustable Contact Adjustment Range:
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts:
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type:
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed:
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Liquid
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Liquid Thread Series Designator:
Actuation point adjustable Contact Adjustment Range: +2.00/+380.00 actuation point pounds per square inch gage Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Liquid Thread Series Designator: Npt single pressure connection

--

NSN 5930-01-189-3583

Pressure Switch - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A048b0