

View Online at <https://aerobasegroup.com/nsn/5930-01-189-5305>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof and corrosion proof and moisture proof

**Overall Length:**

0.840 inches

**Overall Height:**

2.187 inches

**Overall Width:**

0.719 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.840 inches

**Body Width:**

0.719 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

0.640 inches

**Actuator Width:**

0.375 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained and center position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Marine air traffic control landing systems, aircraft orion p-3, aircraft (ac-130h, mc-130h, ec-130e, hc-130)

**Mounting Surface To Terminal End Distance:**

1.077 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0