

View Online at <https://aerobasegroup.com/nsn/5930-01-189-5305>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and corrosion proof and moisture proof

Overall Length:

0.840 inches

Overall Height:

2.187 inches

Overall Width:

0.719 inches

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.719 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.640 inches

Actuator Width:

0.375 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Marine air traffic control landing systems, aircraft orion p-3, aircraft (ac-130h, mc-130h, ec-130e, hc-130)

Mounting Surface To Terminal End Distance:

1.077 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0