

View Online at <https://aerobasegroup.com/nsn/5930-01-189-7601>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

1.140 inches

Overall Height:

2.265 inches

Overall Width:

0.730 inches

Bushing Length:

0.460 inches

Body Length:

1.140 inches

Body Width:

0.730 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.680 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.125 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

8 two circuit, double make, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes motor dc

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

32 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0